

29W LED Downlight



Commercial lighting, Indoor use

- Easy Installation.
- Integrated over temperature protection.
- Ingress protection IP20 rating.
- 5 year warranty.
- No UV and IR Emission.
- Mercury Free.

2500 Lumens	0.95pf Power Factor	(CRI) ≥80Ra Colour Rendering Index	90° Beam Angle
IP20 Ingress Protection	5 Years Warranty	 Easy Installation	 30 000 hr Lifespan
		 Ø 205mm Cut Out Hole	 No UV, No IR Mercury Free

PRODUCT	FL29INTDL	FL29INTC
Input voltage	AC 220V - 240V, 50Hz	
Power factor	>0.95 ±10%	
Total power	29W ±10%	
Colour temperature	5700-6500K ±10% (Daylight)	3800-4250K ±10% (Cool White)
Efficacy	86Lm/W ±10%	
Light output	2500Lm ±10%	
CRI	>80	
Beam angle	90°	
Driver Type	Integrated	
Surge	Line-Line >1kV, Line-GND > 2kV	
Product size (mm)	Diameter: 218mm, Height: 100mm	
Cut Out Hole (∅)	205 - 210mm	
Operating environment	0°C to 40°C	
Dimmable	No	
Rated life	*30 000 hours	
Main materials	Aluminium and PC	

*30 000 hours is the average performance under standard test conditions based on 12 hours use per day. Actual performance may vary depending on usage and working conditions.

Product Code: **FL29INTC**
Barcode: **600284400 4118**



Product Code: **FL29INTDL**
Barcode: **600284406 2903**



PACKAGE CONTENTS

1 x 29W LED downlight

PACKAGE DIMENSIONS

	Height (mm)	Depth (mm)	Width (mm)	Weight (kg)
FL29INTDL	115	242	244	1.64
FL29INTC	115	242	244	1.64